

Safety Precautions

Solidify paint in well-ventilated areas that are inaccessible to children and pets. Do not solidify the paint in a basement or inside the house. If you should feel dizzy or nauseous while working with the paint, take a fresh air break.

Do not solidify paint in a garage or shed where there is an appliance that uses a pilot light, welding activities, light switch, light bulb, electric garage door or any other source of spark or flame. Volatile, reactive or flammable chemicals can concentrate in an inadequately ventilated room. If the room has a source of spark or flame, the airborne chemicals could explode or cause a fire.

Do not smoke or drink alcoholic beverages while solidifying paint. Avoid inhalation of fumes. If you can smell it, you are breathing the product. Wear protective gloves to avoid skin contact while handling the paint.

Procedures

To solidify small quantities, such as an inch or two in the bottom of a can, simply remove the lid, add non-flammable absorbent and stir until all the liquid is absorbed. When the paint is solidified, place the absorbent and paint cans inside a garbage bag, seal the bag tightly and dispose of it in the trash destined for the landfill.

For larger quantities of paint, mix absorbent and paint in a bucket or sturdy cardboard box and stir. It will be easier if you pour some absorbent in the bottom of the container and add the paint slowly while stirring. Continue to alternate the absorbent and paint and stirring. The end product should be similar in texture to the absorbent. When the paint is solidified, place the absorbent and container inside a garbage bag, seal it tightly, and dispose of it in the trash destined for the landfill.

For additional information, please contact the Customer Service Center by dialing (404) 546-0311 or visit <https://www.atl311.com/>.